A one-page tutorial on coherent ν-N scattering

- Uncontroversial Standard Model process
- Large enhancement in cross-section for E_ν < few tens of MeV ($\sigma \propto N^2$, possible only for neutral current)
- However, not yet measured… detector technology has been missing.

Detector mass must be at least ~1 kg (reactor experiment) + *recoil* energy threshold << 1keV

(low-E recoils lose only 10-20% to ionization or scintillation)

- Cryogenic bolometers and other methods proposed, no successful implementation yet

Cabrera, Krauss & Wilczek
Phys. Rev. Lett. 55, 25-28 (1985)
(prehistory of CDMS detectors)



Fundamental physics:

- Largest σ_ν in SN dynamics: should be measured to validate models (J.R. Wilson, PRL 32 (74) 849)
- A large detector can measure total E and T of SN ν_μ, ν_τ ⇒ determination of ν oscillation pattern and mass of ν star (J.F.Beacom, W.M.Far & P.Vogel, PRD 66(02)033011)
- Coherent σ same for all known ν… oscillations observed in a coherent detector ⇒ evidence for $\nu_{sterile}$ (A.Drukier & L.Stodolsky, PRD 30 (84) 2295)
- Sensitive probe of weak nuclear charge ⇒ test of radiative corrections due to new physics above weak scale (L.M.Krauss, PLB 269, 407)
- More sensitive to NSI and new neutral bosons than ν factories. Also effective ν charge ratio (J. Barranco et al., hep-ph/0508299,hep-ph-0512029
- σ critically depends on μ_ν: observation of SM prediction would increase sensitivity to μ_ν by > an order of magnitude (A.C.Dodd *et al*, PLB 266 (91) 434)

Smallish detectors… "ν technology"?

- Monitoring of nuclear reactors against illicit operation or fuel diversion: present proposals using conventional 1-ton detectors reach only > ~3 GWt reactor power
- Geological prospection, planetary tomography… the list gets much wilder.

A one-page tutorial on coherent ν-N scattering

- Uncontroversial Standard Model process
- Large enhancement in cross-section for E_ν < few tens of MeV ($\sigma \propto N^2$, possible only for neutral current)
- However, not yet measured… detector technology has been missing.

Detector mass must be at least ~1 kg (reactor experiment) + *recoil* energy threshold << 1keV

(low-E recoils lose only 10-20% to ionization or scintillation)

- Cryogenic bolometers and other methods proposed, no successful implementation yet



Expected number of neutral-current nuclear recoils in several gases from a typical reactor neutrino flux and spectrum ($10^{13}\nu\,cm^{-2}s^{-1}$)

Gas	Recoils/kg/day	of which $E_{rec}<1$ keV	of which $E_{rec}<100$ eV
He	8.1	3.5	0.6
Ne	43.9	37.0	10.7
Ar	103.2	98.1	39.8
Xe	389.7	389.1	274.1

Fundamental physics:

- Largest σ_ν in SN dynamics: should be measured to validate models (J.R. Wilson, PRL 32 (74) 849)
- A large detector can measure total E and T of SN ν_μ, ν_τ ⇒ determination of ν oscillation pattern and mass of ν star (J.F.Beacom, W.M.Far & P.Vogel, PRD 66(02)033011)
- Coherent σ same for all known ν… oscillations observed in a coherent detector ⇒ evidence for $\nu_{sterile}$ (A.Drukier & L.Stodolsky, PRD 30 (84) 2295)
- Sensitive probe of weak nuclear charge ⇒ test of radiative corrections due to new physics above weak scale (L.M.Krauss, PLB 269, 407)
- More sensitive to NSI and new neutral bosons than ν factories. Also effective ν charge ratio (J. Barranco et al., hep-ph/0508299,hep-ph-0512029
- σ critically depends on μ_ν: observation of SM prediction would increase sensitivity to μ_ν by > an order of magnitude (A.C.Dodd *et al*, PLB 266 (91) 434)

Smallish detectors… "ν technology"?

- Monitoring of nuclear reactors against illicit operation or fuel diversion: present proposals using conventional 1-ton detectors reach only > ~3 GWt reactor power
- Geological prospection, planetary tomography… the list gets much wilder.

A one-page tutorial on coherent ν-N scattering

- Uncontroversial Standard Model process
- Large enhancement in cross-section for E_ν < few tens of MeV ($\sigma \propto N^2$, possible only for neutral current)
- However, not yet measured… detector technology has been missing.

Detector mass must be at least ~1 kg (reactor experiment) + *recoil* energy threshold << 1keV

(low-E recoils lose only 10-20% to ionization or scintillation)

- Cryogenic bolometers and other methods proposed, no successful implementation yet



Fundamental physics:

- Largest σ_ν in SN dynamics: should be measured to validate models (J.R. Wilson, PRL 32 (74) 849)
- A large detector can measure total E and T of SN ν_μ, ν_τ ⇒ determination of ν oscillation pattern and mass of ν star (J.F.Beacom, W.M.Far & P.Vogel, PRD 66(02)033011)
- Coherent σ same for all known ν… oscillations observed in a coherent detector ⇒ evidence for $\nu_{sterile}$ (A.Drukier & L.Stodolsky, PRD 30 (84) 2295)
- Sensitive probe of weak nuclear charge ⇒ test of radiative corrections due to new physics above weak scale (L.M.Krauss, PLB 269, 407)
- More sensitive to NSI and new neutral bosons than ν factories. Also effective ν charge ratio (J. Barranco et al., hep-ph/0508299,hep-ph-0512029
- σ critically depends on μ_ν: observation of SM prediction would increase sensitivity to μ_ν by > an order of magnitude (A.C.Dodd *et al*, PLB 266 (91) 434)

Smallish detectors… "ν technology"?

- Monitoring of nuclear reactors against illicit operation or fuel diversion: present proposals using conventional 1-ton detectors reach only > ~3 GWt reactor power
- Geological prospection, planetary tomography… the list gets much wilder.

A one-page tutorial on coherent ν-N scattering

- Uncontroversial Standard Model process
- Large enhancement in cross-section for E_ν < few tens of MeV ($\sigma \propto N^2$, possible only for neutral current)
- However, not yet measured… detector technology has been missing.

Detector mass must be at least ~1 kg (reactor experiment) + *recoil* energy threshold << 1keV

(low-E recoils lose only 10-20% to ionization or scintillation)

- Cryogenic bolometers and other methods proposed, no successful implementation yet



Fundamental physics:

- Largest σ_ν in SN dynamics: should be measured to validate models (J.R. Wilson, PRL 32 (74) 849)
- A large detector can measure total E and T of SN ν_μ, ν_τ ⇒ determination of ν oscillation pattern and mass of ν star (J.F.Beacom, W.M.Far & P.Vogel, PRD 66(02)033011)
- Coherent σ same for all known ν… oscillations observed in a coherent detector ⇒ evidence for $\nu_{sterile}$ (A.Drukier & L.Stodolsky, PRD 30 (84) 2295)
- Sensitive probe of weak nuclear charge ⇒ test of radiative corrections due to new physics above weak scale (L.M.Krauss, PLB 269, 407)
- More sensitive to NSI and new neutral bosons than ν factories. Also effective ν charge ratio (J. Barranco et al., hep-ph/0508299,hep-ph-0512029
- σ critically depends on μ_ν: observation of SM prediction would increase sensitivity to μ_ν by > an order of magnitude (A.C.Dodd *et al*, PLB 266 (91) 434)

Smallish detectors… "ν technology"?

- Monitoring of nuclear reactors against illicit operation or fuel diversion: present proposals using conventional 1-ton detectors reach only > ~3 GWt reactor power
- Geological prospection, planetary tomography… the list gets much wilder.

A one-page tutorial on coherent ν-N scattering

- Uncontroversial Standard Model process
- Large enhancement in cross-section for E_ν < few tens of MeV ($\sigma \propto N^2$, possible only for neutral current)
- However, not yet measured… detector technology has been missing.

Detector mass must be at least ~1 kg (reactor experiment) + *recoil* energy threshold << 1keV

(low-E recoils lose only 10-20% to ionization or scintillation)

- Cryogenic bolometers and other methods proposed, no successful implementation yet

Nieto et al., Nuclear Science and Engineering: ***149*** *(2005)*



Fundamental physics:

- Largest σ_ν in SN dynamics: should be measured to validate models (J.R. Wilson, PRL 32 (74) 849)
- A large detector can measure total E and T of SN ν_μ, ν_τ ⇒ determination of ν oscillation pattern and mass of ν star (J.F.Beacom, W.M.Far & P.Vogel, PRD 66(02)033011)
- Coherent σ same for all known ν… oscillations observed in a coherent detector ⇒ evidence for $\nu_{sterile}$ (A.Drukier & L.Stodolsky, PRD 30 (84) 2295)
- Sensitive probe of weak nuclear charge ⇒ test of radiative corrections due to new physics above weak scale (L.M.Krauss, PLB 269, 407)
- More sensitive to NSI and new neutral bosons than ν factories. Also effective ν charge ratio (J. Barranco et al., hep-ph/0508299,hep-ph-0512029
- σ critically depends on μ_ν: observation of SM prediction would increase sensitivity to μ_ν by > an order of magnitude (A.C.Dodd *et al*, PLB 266 (91) 434)

Smallish detectors… "ν technology"?

- Monitoring of nuclear reactors against illicit operation or fuel diversion: present proposals using conventional 1-ton detectors reach only > ~3 GWt reactor power
- Geological prospection, planetary tomography… the list gets much wilder.

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Three legged stool needed: mass, threshold, background



No "light-bulb" moment:
5 years of R&D at UC



13 cm^2 APD on a 2 inch diameter silicon wafer



name-of-the-game:
detection of << 1 keV recoils with large (> 1 kg) detectors

(25 y and counting... must use new technologies or at least alterations)



Mass-produced 3M-UoC GEM and single-electron signals from quadruple GEM

Single-photon pulses using LN_2 cooled LAAPDs (high QE)

Start with the foundations: ultra low-energy recoil calibrations at KSU reactor

Kavli Institute for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO



24 keV n's mimic reactor ν's

Fe-Al filter + Ti post-filter





MCNP filter design



Start with the foundations: ultra low-energy recoil calibrations at KSU reactor

Kavli Institute for Cosmological Phy
AT THE UNIVERSITY OF CHICAGO



Ti post-filter "switches off" the recoils, leaving all backgrounds unaffected



p-recoil spectrometer measurements

← Beam characterization studies completed 2005 (submitted to Phys. Rev. C)

Ideal to explore sub-keV recoil region →



Kavli Institute

Modified-electrode p-type HPGe: A new tool in astroparticle & neutrino physics



Fig. 3. Structure of the shaped-field detector.

Now a p-type (much enhanced E resolution, less sensitivity to low-E backgrounds)

1989 state-of-the-art in large HPGe noise:
300 eV FWHM (even with modified electrode)

The idea: we have gone a long ways in JFET technology

2005: (factor x10 improvement in JFET C_F and V_n)
~50 eV FWHM (same as C_D~1 pF x-ray detectors)

$$FWHM_{Ge} = 40.7\ eV \cdot V_n (C_F + C_D)/\sqrt{\Delta t}$$

~1985 **(TI 2N4416)** $C_F = 4.2$ pF, $V_n = 2$ nV/$\sqrt{Hz}$

2005 **(EuriFET ER105)** $C_F = 0.9$ pF, $V_n = 1.6$ nV/$\sqrt{Hz}$

Kavli Institute

Modified-electrode p-type HPGe: A new tool in astroparticle & neutrino physics



Fig. 3. Structure of the shaped-field detector.

Developed for "Cosmion" searches.

Now a p-type (much enhanced E resolution, less sensitivity to low-E backgrounds)

1989 state-of-the-art in large HPGe noise:
300 eV FWHM (even with modified electrode)

The idea: we have gone a long ways in JFET technology

2005: (factor x10 improvement in JFET C_F and V_n)
~50 eV FWHM (same as C_D~1 pF x-ray detectors)

$$FWHM_{Ge} = 40.7\ eV \cdot V_n (C_F + C_D)/\sqrt{\Delta t}$$

~1985 (TI 2N4416) $C_F = 4.2$ pF, $V_n = 2$ nV/$\sqrt{Hz}$

2005 (EuriFET ER105) $C_F = 0.9$ pF, $V_n = 1.6$ nV/$\sqrt{Hz}$

The energy resolution and large mass of a HPGe plus the noise and threshold of a tiny x-ray detector???

Kavli Institute

Modified-electrode p-type HPGe: A new tool in astroparticle & neutrino physics



Fig. 3. Structure of the shaped-field detector.

Now a p-type (much enhanced E resolution, less sensitivit to low-E backgrounds)

1989 state-of-the-art in large HPGe noise:
300 eV FWHM (even with modified electrode)

The idea: we have gone a long ways in JFET technology

2005: (factor x10 improvement in JFET C_F and V_n)
~50 eV FWHM (same as C_D~1 pF x-ray detectors)

$$FWHM_{Ge} = 40.7\ eV \cdot V_n (C_F + C_D)/\sqrt{\Delta t}$$

~1985 (TI 2N4416) $C_F = 4.2$ pF, $V_n = 2$ nV/$\sqrt{Hz}$

2005 (EuriFET ER105) $C_F = 0.9$ pF, $V_n = 1.6$ nV/$\sqrt{Hz}$



~x10 less noise than conventional HPGe of same mass (475 g) (threshold equivalent to 5 g x-ray detector)

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Precise gradient of
charged impurities
along the axis
needed to compensate for
small electrode

E. E. Haller *et al.* Adv. in Phys. 30(81)93

Fig. 1



Net-shallow level concentration $|N_A - N_D|$ along the growth axis of an ultra-pure germanium single crystal. At the seed end (0% of melt frozen) the aluminium acceptor dominates, yielding the crystal p-type. Near the tail end the phosphorus concentration exceeds the aluminium concentration. $|N_A - N_D|$: continuous curve; aluminium concentration: dashed curve; phosphorus concentration: dotted curve.

Delivered-To: collar@cfcp.uchicago.edu
Subject: Re: update?
From: otench@canberra.com
To: "Juan I. Collar" <collar@uchicago.edu>
Date: Sat, 3 Dec 2005 16:41:10 -0500
X-Uchicago-PMX-Id: 192.153.25.189: jB3LtheQ001154 [Sat Dec 3 15:55:44 2005]
X-Uchicago-Spam: Gauge=XXI, Probability=21%

Hello Juan,
We just got the first results in and they seem to be outstanding. The pulse resolution is about 160eV(FWHM) and Co-60 is well under 2.0 KV(FWHM). The detector should be shipping from France soon- in time for Christmas. It is too late now to change hardware but this mignt be done in future.

Best regards, Orren

Developed during 2005
by CANBERRA/EURYSIS
(the one of three contacted companies up to the challenge)
Funded by NNSA.

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Mass and threshold in place for reactor experiment, background… almost there (anti-Compton shield & Al part replacement underway)



Expected antineutrino signal in reactor experiment with present detector.
Background goal shown
(scaled down from present status)

Presently 2.5 ν recoils/kg-day expected
Work on non-white noise can increase this to >30 ν recoils/kg-day
(limited by state-of-the-art JFET noise only)



Silver lining: all of the signal concentrated in small ROI

Extensive detector characterization early 2006
(submitted to Phys. Rev. C)







Shielding studies at 6 m.w.e. (comparable to reactor site)

Extensive detector characterization early 2006
(submitted to Phys. Rev. C)

Kavli Institute
for Cosmological Physics
AT THE UNIV



This is the state-of-the-art for 1 pF detectors!

(Pentafet)

We can do better





Shielding studies at 6 m.w.e. (comparable to reactor site)

Extensive detector characterization early 2006
(submitted to Phys. Rev. C)

Kavli Institute
for Cosmological Physics
AT THE UNIV



This is the state-of-the-art for 1 pF detectors!

(Pentafet)

We can do better





Shielding studies at 6 m.w.e. (comparable to reactor site)

Some recent news: looking very good…







Some recent news: looking very good...

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Relevant ROI for power reactor experiment has been explored





Excess signal (only) in coincidence with (strictly) the thermal Li-6 peak and (only) in the absence of Ti post-filter: very convincing signature

Mass √

Threshold √

Background... (on it)

The Kavli Foundation

Some recent news: looking very good...

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Definitive check on DAMA soon
X50 improvement from clean Al, x10 from anti-Compton



First Physics Results expected Fall 06:

These light WIMPs remain compatible with DAMA & all other searches (accelerator bounds are model-dependent)

Next: replacement with <0.2 ppb U cryostat, develop low-bckg version of anti-Compton shield... and deploy to power reactor.

Nothing radioclean yet (need cash! ☹)

The Kavli Foundation

What else can you do with such a detector?

J.I. Collar PRD 59 063514
Damour & Krauss PRL 81 5726

Kavli Institute for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Solar-bound WIMPs: deposit ~x100 less E_{rec} than galaxy-bound, concentrate all rate in narrow spectral region (higher s/n)
Sub-keV threshold a must







Gelmini, Kusenko, Nussinov
PRL 89 (02) 101302

The neutralino is not the only supersymmetric Dark Matter candidate. Non-pointlike DM (Q-balls, Mirror matter, etc.) call for ultra-low threshold detectors



Improved sensitivity to ν magnetic moment (reactor experiment)

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

MAJORANA: can we avoid segmentation altogether?
(cost, speed, simplicity, much lower front-end backgrounds)
Does this device have anything to offer in a ββ context?

Optimal E-resolution allows one to think ββ ...



Compare resolution with n-type 1989
(now same as coax HPGe of same mass, 1.8KeV FWHM)





Also x20 improvement in charge collection in going to p-type

The Kavli Foundation

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

How does a multiple-site interaction look in a modified-electrode HPGe?



Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

That was then...



Coaxial Ge Detector Configuration

TOP: preamp trace
BOTTOM: 10ns int.+ diff. TFA
(follows charge arrival)



Limited ability to distinguish singles from multiples (one bump or two?)

The Kavli Foundation

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

This is now.



Different hits get clearly stretched in time.



All this with optimal energy resolution and charge collection (and one channel)

What is happening?



standard coaxial HPGe



P-type modified electrode





Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Better signal acceptance / background rejection than an 8-segment clover HPGe (even before close packing!) all with a single-channel device





Kavli Institute for Cosmological Physics AT THE UNIVERSITY OF CHICAGO

Advantages of single channel p-type modified electrode vis-à-vis segmentation for MAJORANA:

- Very efficient PSA rejection of multiples. All with one channel.
- Excellent energy resolution (1.8 keV Co-60, may drop some as noise is further improved)
- Increase speed of deployment/manufacture as long as... (is gradient of impurities reproducible? How important?)
- Increase simplicity of construction and analysis (one channel)
- Decrease cost (detectors and DAQ). Improve production time (cosmogenics)
- Decrease front end-associated radioactive backgrounds, thermal load, photon path.
- Increase stability (prototype performance stable for >5 continuous mo. and counting)
- Intrinsic to p-type: ruggedness (a must when arraying) and decreased sensitivity to surface contaminations.
- Several others (e.g., rejection of ALL alphas via PIXE -studies underway-)
- CANBERRA and PHDs Co. receptive to further fabrication (and further work on noise reduction).

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Disadvantages:

- Technology too new: too many unknowns in reproducibility, cost, speed of production, largest crystal size that can be produced, waste (important for $\beta\beta$), etc.
- Canberra's position: We need to build 6-10 more to know (they admit "lucking out". Hopefully this will not change).

Solution:

- This fits perfectly with planned coherent ν program. Upcoming NSF proposal (3 yr) will be centered around this theme <- Help from rest of MAJORANA collaboration to maximize **synergy**: PNNL already funded to build more of these, ORNL seeking funding.
- Several kg of modified-electrode p-type HPGe's built by 2007!
- GOAL: Be by early next year counting at the Columbia Generating Station (Richland, WA, 12 mi. from PNNL) and simultaneously further developing the technique (i.e., building more of these). San Onofre? (offers more depth)

NSF
National Nuclear Security Administration
The Kavli Foundation

Kavli Institute for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Reactor Monitoring: Right technological timing (HPGe technology flourishing: segmentation, encapsulation, arrays and (silent) mechanical cooling)

CLUSTER





MAJORANA

RHESSI





GERDA

The Kavli Foundation

Kavli Institute for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Reactor Monitoring: Right technological timing (HPGe technology flourishing: segmentation, encapsulation, arrays and (silent) mechanical cooling)



New generation of recondensing Dewars add no microphonic noise and need topping (not refilling) every ~ 1yr (can be filled from N2 gas cylinder!) Ideal for reactor deployment.

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

11 kg,
encapsulated,
single cold finger
(CANBERRA)

A reality
fast approaching?



With 100 eV threshold,
the equivalent
of ~1 ton
liquid scintillator



CLUSTER array for EUROBALL
(7 encapsulated HPGe detectors)

Hexagonal tapering - diam.: 70 mm - height: 78 mm
FWHM resolution : ≤ 2.3 keV
Efficiency: ≥ 55%
Alu wall thickness: 0.7 mm
Cap-to-Ge distance: 0.7 mm.

SANDS Sees Reactor Turn-on in Detail
(Antineutrino Rate, Running Average)



The Kavli Foundation

Kavli Institute
for Cosmological Physics
AT THE UNIVERSITY OF CHICAGO

Coherent neutrino detection:

I want to believe!